

## Customized Designed

Multiple options to meet your specific needs

## Transportation Ranges

Loadbanks fitted for local or nationwide transport

## Multiple Trailer Types

Flat-deck, step-deck and container chassis options



## Trailer Specifications

### Trailer Type

Flat-deck with pintle hitch and electric breaks, step-deck and 20' container chassis with fifth wheel hitch and air breaks

### Axles

Triple or double

### Suspension

Standard or air-ride

### Securing Method

Chains and binders or corner locks

### GVWR

30,000 or 65,000 lbs.

### Orientation

Front or rear facing bussbar

### Trailer Weight

From 4,000 lbs up to 6,400 lbs.

### Loadbank Height

Range between 27" and 50"

### Dimensions

Total length/width between 223"/103" and 282"/96"  
Deck length/width between 143.5"/77.5" and unit with chassis

*Materials and specifications are subject to change without notice.*

**it works. every time.**

**877.838.1088**

**hps**loadbanks.com  
sales and rentals



## Trailer Configuration Options

	Flat-Deck	Flat-Deck	Step-Deck	20' Container Chassis
<b>Unit Range</b>	<b>1.875MVA and below</b>	<b>1.875MVA / 3.3MVA</b>	<b>3.3MVA</b>	<b>6.25MVA</b>
Weight of Trailer	4,000 lbs (Approx.)	11,890 lbs	7,700 lbs	6,400 lbs
GVWR	—	—	30,000 lbs	65,000 lbs
Hitch Type	Pintle	Fifth wheel	Fifth wheel	Fifth wheel
Brakes	Electric	Air	Air	Air
Total Length	223"	198"	300"	282"
Deck Length	143.5"	480"	120"	No usable deck space
Total Width	103"	96"	96"	96"
Deck Width	77.5"	96"	96"	Chassis only
Height of Loadbank	27"	37"	36"	50"
Securing Loadbank	Chains & binders	Corner locks	Corner locks	Corner locks
Axles	Triple	Double	Double	Double
Suspension	Standard	Air-ride	Air-ride	Air-ride
Orientation of Loadbank	Front or rear facing bussbar	Front or rear facing bussbar	Front or rear facing bussbar	Front or rear facing bussbar
Restrictions / Notes	Local use only	Pintle with air brakes	None	None

*Materials and specifications are subject to change without notice.*